


DS-KH9570-WTE1/F
DS-KH9570-WTE1/F




- Integrated Smart Security Unified security management on single screen
- Ultra Smooth Operation: • 4-core processor • Android 14 • Up to 4 GB RAM + 8 GB ROM
- Super HD Clarity: • 10.1" IPS touch display • 1920×1200 resolution
- Real Talk Anytime: • Dual microphones & speakers • Noise suppression and echo cancellation

▪ Specification

System parameters	
Operation system	Android 14
ROM	8 GB
RAM	4GB
Processor	Embedded high performance processor
Display parameters	
Screen size	10.1-inch
Operation method	Capacitive touch screen
Type	Colorful IPS
Resolution	1920 ×1200
Video parameters	
Lens	/
Resolution	/
Video compression standard	/
Audio parameters	
Audio input	2 built-in omnidirectional microphone
Audio compression standard	G.711A, G.711U, G.722.1, G726, Opus, AAC, AAC_LD
Audio output	2 built-in loudspeaker (Max. 80dB@50cm)
Audio compression bitrate	64 Kbps
Audio quality	Noise suppression and echo cancellation
Volume adjustment	Adjustable
Capacity	
Linked doorphone capacity	17
Message capacity	200 captured pictures, 200 alarm records, 200 unlock records, 200 temper records
Linked indoor extensions capacity	16
Linked network camera capacity	16 (Up to 4 1080P decoding streams at the same time, H.264&H.265)
Network parameters	
Wi-Fi	Wi-Fi 6, 2.4 GHz & 5GHz
Bluetooth	BLE 5.0
Network protocol	IPv4, SIP, HTTP, HTTPS, DNS, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP SIP v1 (RFC2543), SIP v2 (RFC3261) DTMF: SIP Info SADP, ISAPI, ONVIF
Device interfaces	
Alarm input	2 (Reserved)
Network interface	1 RJ-45 10/100 Mbps self-adaptive
RS-485	/
TF card	Support TF card (FAT32/exFAT), up to 256 G
Power supply input	12 VDC
Power supply output	/
Relay	/
General	
Proximity Sensor	Distance: 50cm, Horizontal: 25°, Vertical: 25°
Installation	Flush mounting

Weight	Without package: 548 g (1.21 lb),With package: 920g (2.03 lb)
Working temperature	-10 °C to 50 °C (14 °F to 122 °F)
Working humidity	10% to 90% (no-condensing)
Power supply	12 VDC, 2.5 A; IEEE 802.3at, Standard PoE
Application environment	Indoor
Power consumption	≤ 24 W
Language	English, Arabic, French, Russian, Spanish, Spanish (Latin America), Italian, German, Polish, Turkish, Portuguese, Portuguese (Brazil), Uzbek, Kazakh, Czech, Hungarian, Dutch, Romanian, Bulgarian, Ukrainian, Croatian, Serbian, Greek, Lithuanian, Estonian, Latvian, Norwegian, Danish, Slovenian, Slovak, Hebrew, Swedish, Finnish, Mongolian, Vietnamese, Traditional Chinese
Dimension (W × H × D)	246.58 mm × 155.76 mm × 11.82 mm (9.71" × 6.13" × 0.47") (Out of the wall)

▪ Dimension



Unit:mm [inch]

SCALE 1:1

See Far, Go Further



www.hikvision.com
support@hikvision.com

