


IPMECD-S-L-M4560

Telescopic Straight Arm



- 4.5 to 6 m (14.76 ft to 19.69 ft) telescopic arm, suitable for both side of the barrier gate. Made of aluminum alloy with electrostatic powder coating for rust prevention. Main arm section features red/green LED strip lighting and a flexible anti-smash rubber strip at the base.

Series Overview

Constructed from highly durable aluminum alloy, the Barrier Rod features an advanced anti-rust coating on its surface. Additionally, it is equipped with an elastic anti-collision rubber strip at the bottom for added protection.

Technical Specification

Basic

Matched Product	DHI-IPMECD-2062 series barrier
-----------------	--------------------------------

General

Operating Temperature	−40 °C to +70 °C (−40 °F to +158 °F)
Storage Temperature	−40 °C to +70 °C (−40 °F to +158 °F)
Operating Humidity	10%–90% (RH), non-condensing
Storage Humidity	10%–90% (RH), non-condensing
Casing Material	Metal (aluminium)
Product Dimensions	3600 mm × 100 mm × 45 mm (141.73" × 3.94" × 1.77") (L × W × H)
Packaging Dimensions	3700 mm × 150 mm × 100 mm (145.67" × 5.91" × 3.94") (L × W × H)
Net Weight	6.9 kg (15.21 lb)
Gross Weight	7.4 kg (16.31 lb)
Installation	Install onto the matching barrier
Anti-corrosion Level	Basic Protection *The products are designed for general use and are applicable even in areas with no specific requirements for anti-corrosion protection.

Ordering Information

Type	Model	Description
Barrier Rod	IPMECD-S-L-M4560	Telescopic Straight Arm

Dimensions (mm[inch])

