

**DS-2CD2347G3-LIS2UY/SL****4 MP Smart Hybrid Light with ColorVu Fixed Turret Network Camera****ColorVu 3.0**

Hikvision products are classified into three levels according to their anti-corrosion performance. Refer to the following description to choose for your using environment.

- HikAI-ISP for excellent noise reduction effect
- 24/7 colorful imaging via ColorVu technology
- Scene-adaptive WDR
- Focus on Person and Vehicle classification based on deep learning
- Built-in arrayed dual-microphone for real-time high quality audio security
- Provide real-time security via built-in two-way audio
- Anti-corrosion design, providing reliability and longevity compared to standard (NEMA4 X)
- Smart Hybrid Light: Integrates IR and White lights, 3 supplemental lighting modes
- Water and dust resistant (IP67)
- Audio and alarm interface available
- Active strobe light and audio alarm to warn intruders off

## ▪ Specification

| Camera                      |                                                                                                                                                                                          |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Image Sensor                | 1/1.8" Progressive Scan CMOS                                                                                                                                                             |
| Max. Resolution             | 2688 × 1520                                                                                                                                                                              |
| Min. Illumination           | Color: 0.0001 Lux @ (F1.0, AGC ON), 0 Lux with light                                                                                                                                     |
| Shutter Time                | 1 s to 1/100,000 s                                                                                                                                                                       |
| Day & Night                 | IR cut filter                                                                                                                                                                            |
| Angle Adjustment            | Pan: 0° to 360°, tilt: 0° to 75°, rotate: 0° to 360°                                                                                                                                     |
| Lens                        |                                                                                                                                                                                          |
| Lens Type                   | Fixed focal lens, 2.8 and 4 mm optional                                                                                                                                                  |
| Focal Length & FOV          | 2.8 mm, horizontal FOV 111.1°, vertical FOV 57.6°, diagonal FOV 138.5°<br>4 mm, horizontal FOV 95.2°, vertical FOV 48.3°, diagonal FOV 117.4°                                            |
| Lens Mount                  | M16                                                                                                                                                                                      |
| Iris Type                   | Fixed                                                                                                                                                                                    |
| Aperture                    | F1.0                                                                                                                                                                                     |
| Depth of Field              | 2.8 mm: 2.5 m to ∞<br>4 mm: 3.1 m to ∞                                                                                                                                                   |
| DORI                        |                                                                                                                                                                                          |
| DORI                        | 2.8 mm: D: 61 m, O: 24 m, R: 12 m, I: 6 m<br>4 mm: D: 75 m, O: 30 m, R: 15 m, I: 7 m                                                                                                     |
| Illuminator                 |                                                                                                                                                                                          |
| Supplement Light Type       | White Light, IR                                                                                                                                                                          |
| Supplement Light Range      | Up to 30 m                                                                                                                                                                               |
| Smart Supplement Light      | Yes                                                                                                                                                                                      |
| IR Wavelength               | 850 nm                                                                                                                                                                                   |
| Video                       |                                                                                                                                                                                          |
| Main Stream                 | 50 Hz: 25 fps (2688 × 1520, 1920 × 1080, 1280 × 720)<br>60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720)                                                                             |
| Sub-Stream                  | 50 Hz: 25 fps (1280 × 720, 640 × 480, 640 × 360)<br>60 Hz: 30 fps (1280 × 720, 640 × 480, 640 × 360)                                                                                     |
| Third Stream                | 50 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)<br>60 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)<br>*The third stream is supported under certain settings. |
| Video Compression           | Main stream: H.265/H.264/H.264+/H.265+,<br>Sub-stream: H.265/H.264/MJPEG,<br>Third stream: H.265/H.264,<br>*Third stream is supported under certain settings.                            |
| Video Bit Rate              | 32 Kbps to 8 Mbps                                                                                                                                                                        |
| H.264 Type                  | Baseline Profile, Main Profile, High Profile                                                                                                                                             |
| H.265 Type                  | Main Profile                                                                                                                                                                             |
| Bit Rate Control            | CBR, VBR                                                                                                                                                                                 |
| Scalable Video Coding (SVC) | H.264 and H.265 encoding                                                                                                                                                                 |
| Region of Interest (ROI)    | 1 fixed region for main stream                                                                                                                                                           |
| Audio                       |                                                                                                                                                                                          |
| Audio Type                  | Mono sound                                                                                                                                                                               |
| Audio Compression           | G.711/G.722.1/G.726/MP2L2/PCM/MP3/AAC-LC                                                                                                                                                 |

|                             |                                                                                                                                                                                                                                                                                                                                                                                       |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Audio Bit Rate              | 64 Kbps (G.711ulaw/G.711alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 192 Kbps (MP2L2)/8 to 320 Kbps (MP3)/16 to 64 Kbps (AAC-LC)                                                                                                                                                                                                                                                     |
| Audio Sampling Rate         | 8 kHz/16 kHz/32 kHz/48 kHz                                                                                                                                                                                                                                                                                                                                                            |
| Environment Noise Filtering | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Network</b>              |                                                                                                                                                                                                                                                                                                                                                                                       |
| Protocols                   | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, WebSocket, WebSockets, SRTP, SFTP                                                                                                                                                                                               |
| Simultaneous Live View      | Up to 6 channels                                                                                                                                                                                                                                                                                                                                                                      |
| API                         | ONVIF (ProfileS, Profile G, Profile T), ISAPI, SDK, ISUP                                                                                                                                                                                                                                                                                                                              |
| User/Host                   | Up to 32 users<br>3 user levels: administrator, operator, and user                                                                                                                                                                                                                                                                                                                    |
| Security                    | Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-TLS, EAP-LEAP, EAP-MD5), watermark, IP address filter, basic and digest authentication for HTTP/HTTPS, WSSE and digest authentication for Open Network Video Interface, RTP/RTSP over HTTPS, control timeout settings, security audit log, TLS 1.1/1.2/1.3, host authentication (MAC address) |
| Network Storage             | NAS (NFS, SMB/CIFS), Auto Network Replenishment (ANR)                                                                                                                                                                                                                                                                                                                                 |
| Client                      | iVMS-4200, Hik-Connect, Hik-Central                                                                                                                                                                                                                                                                                                                                                   |
| Web Browser                 | Plug-in free live view: Chrome 80+, Firefox 80+, Edge 89+,<br>Local service: Chrome 80+, Firefox 80+, Edge 89+                                                                                                                                                                                                                                                                        |
| <b>Image</b>                |                                                                                                                                                                                                                                                                                                                                                                                       |
| Image Parameters Switch     | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| Image Settings              | Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance, adjustable by client software or web browser                                                                                                                                                                                                                                                           |
| Day/Night Switch            | Day, Night, Auto, Schedule                                                                                                                                                                                                                                                                                                                                                            |
| Image Enhancement           | BLC, HLC, 3D DNR, Distortion Correction, Defog                                                                                                                                                                                                                                                                                                                                        |
| SNR                         | ≥ 52 dB                                                                                                                                                                                                                                                                                                                                                                               |
| Wide Dynamic Range (WDR)    | 130 dB                                                                                                                                                                                                                                                                                                                                                                                |
| Image Stabilization         | EIS                                                                                                                                                                                                                                                                                                                                                                                   |
| Privacy Mask                | 4 programmable polygon privacy masks                                                                                                                                                                                                                                                                                                                                                  |
| <b>Interface</b>            |                                                                                                                                                                                                                                                                                                                                                                                       |
| Ethernet Interface          | 1 RJ45 10 M/100 M self-adaptive Ethernet port                                                                                                                                                                                                                                                                                                                                         |
| On-Board Storage            | Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB                                                                                                                                                                                                                                                                                                     |
| Built-in Speaker            | Max. power consumption: 2 W, max. sound pressure level: 10 cm: 110 dB.                                                                                                                                                                                                                                                                                                                |
| Audio                       | Built-in Microphone: Arrayed dual-microphone<br>1 input (line in), two-core terminal block, max. input amplitude: 3.3 Vpp, input impedance: 4.7 KΩ, interface type: non-equilibrium,<br>1 output (line out), two-core terminal block, max. output amplitude: 3.3 Vpp, output impedance: 100 Ω, interface type: non-equilibrium                                                        |
| Alarm                       | 1 input, 1 output (max. 24 VDC/24 VAC, 1 A)                                                                                                                                                                                                                                                                                                                                           |
| Reset Key                   | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Event</b>                |                                                                                                                                                                                                                                                                                                                                                                                       |
| Basic Event                 | Motion detection (support alarm triggering by specified target types (human and vehicle)), video tampering alarm, exception                                                                                                                                                                                                                                                           |
| Smart Event                 | Scene change detection                                                                                                                                                                                                                                                                                                                                                                |

|                                  |                                                                                                                                                                                                                                                                                                                                                       |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Linkage                          | Upload to FTP/NAS/memory card, notify surveillance center, send email, trigger alarm output, trigger recording, trigger capture, audible warning, strobe light flashing                                                                                                                                                                               |
| <b>Deep Learning Function</b>    |                                                                                                                                                                                                                                                                                                                                                       |
| Face Capture                     | Yes                                                                                                                                                                                                                                                                                                                                                   |
| Perimeter Protection             | Line crossing, intrusion, region entrance, region exiting<br>Support alarm triggering by specified target types (human and vehicle)                                                                                                                                                                                                                   |
| <b>General</b>                   |                                                                                                                                                                                                                                                                                                                                                       |
| Power                            | 12 VDC $\pm$ 25%, 1.29 A, max. 15.5 W, $\varnothing$ 5.5 mm coaxial power plug, reverse polarity protection,<br>PoE: IEEE 802.3at, Class 4, max. 17 W                                                                                                                                                                                                 |
| Material                         | Cover: metal, main body: metal                                                                                                                                                                                                                                                                                                                        |
| Dimension                        | $\varnothing$ 138.3 mm $\times$ 115.4 mm ( $\varnothing$ 5.4" $\times$ 4.5")                                                                                                                                                                                                                                                                          |
| Package Dimension                | 170 mm $\times$ 170 mm $\times$ 160 mm (6.7" $\times$ 6.7" $\times$ 6.3")                                                                                                                                                                                                                                                                             |
| Weight                           | Approx. 820 g (1.8 lb.)                                                                                                                                                                                                                                                                                                                               |
| With Package Weight              | Approx. 1200 g (2.6 lb.)                                                                                                                                                                                                                                                                                                                              |
| Storage Conditions               | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)                                                                                                                                                                                                                                                                             |
| Startup and Operating Conditions | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)                                                                                                                                                                                                                                                                             |
| General Function                 | Heartbeat, mirror, flash log, password reset via email, pixel counter, anti-banding                                                                                                                                                                                                                                                                   |
| Language                         | 33 languages: English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil), Ukrainian |
| Flashing Light                   | /SRB model: Red and Blue Light<br>/SL model: White Light                                                                                                                                                                                                                                                                                              |
| <b>Approval</b>                  |                                                                                                                                                                                                                                                                                                                                                       |
| EMC                              | CE-EMC: EN 55032:2015+A1:2020, EN 50130-4:2011+A1:2014, EN IEC 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021,<br>RCM: AS/NZS CISPR 32: 2015,<br>IC: ICES-003: Issue 7,<br>KC: KN32: 2015, KN35: 2015                                                                                                                                      |
| Safety                           | UL: UL 62368-1,<br>CB: IEC 62368-1: 2014+A11,<br>CE-LVD: EN 62368-1: 2014/A11: 2017                                                                                                                                                                                                                                                                   |
| Environment                      | CE-RoHS: 2011/65/EU                                                                                                                                                                                                                                                                                                                                   |
| Protection                       | IP67: IEC 60529-2013                                                                                                                                                                                                                                                                                                                                  |
| Anti-Corrosion Protection        | NEMA 4X (NEMA 250-2018)                                                                                                                                                                                                                                                                                                                               |

## ▪ Typical Application


Hikvision products are classified into three levels according to their anti-corrosion performance. Refer to the following description to choose for your using environment.

This model has MODERATE PROTECTION.

| Level                | Description                                                                                                                                                              |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Top-level protection | Hikvision products at this level are equipped for use in areas where professional anti-corrosion protection is a must. Typical application scenarios include coastlines, |

|                        |                                                                                                                                                                                                                                                        |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                        | docks, chemical plants, and more.                                                                                                                                                                                                                      |
| Moderate protection    | Hikvision products at this level are equipped for use in areas with moderate anti-corrosion demands. Typical application scenarios include coastal areas about 2 kilometers (1.24 miles) away from coastlines, as well as areas affected by acid rain. |
| No specific protection | Hikvision products at this level are equipped for use in areas where no specific anti-corrosion protection is needed.                                                                                                                                  |

## ▪ Dimension



## ▪ Accessory

### ▪ Optional

| DS-1273ZJ-140B-Y                                                                    | DS-1275ZJ-S-SUS                                                                     | DS-1276ZJ-SUS                                                                       | DS-1275ZJ-SUS                                                                         | DS-1271ZJ-140-Y                                                                       |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |  |
| DS-1273ZJ-140-Y                                                                     | DS-1475ZJ-SUS                                                                       | DS-220AZJ-145-WA<br>Y                                                               | DS-1476ZJ-SUS                                                                         | DS-1280ZJ-PT6-Y                                                                       |



## ■ Installation Methods

|                                                                         |                                                                                 |                                                                  |                                                                           |                                                                                        |
|-------------------------------------------------------------------------|---------------------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| <b>Wall Mounting</b><br><b>DS-1273ZJ-140B-Y+DS-1280ZJ-PT6-Y</b>         | <b>Wall Mounting</b><br><b>DS-1273ZJ-140-Y</b>                                  | <b>Wall Mounting</b><br><b>DS-220AZJ-145-WAY</b>                 | <b>Vertical Pole Mounting</b><br><b>DS-1275ZJ-S-SUS+DS-220AZJ-145-WAY</b> | <b>Vertical Pole Mounting</b><br><b>DS-1275ZJ-SUS+DS-1280ZJ-PT6-Y+DS-1273ZJ-140B-Y</b> |
|                                                                         |                                                                                 |                                                                  |                                                                           |                                                                                        |
| <b>Vertical Pole Mounting</b><br><b>DS-1475ZJ-SUS+DS-220AZJ-145-WAY</b> | <b>Corner Mounting</b><br><b>DS-1276ZJ-SUS+DS-1280ZJ-PT6-Y+DS-1273ZJ-140B-Y</b> | <b>Corner Mounting</b><br><b>DS-1476ZJ-SUS+DS-220AZJ-145-WAY</b> | <b>Pendant Mounting</b><br><b>DS-1271ZJ-140-Y+DS-1280ZJ-PT6-Y</b>         | <b>Junction Box</b><br><b>DS-1280ZJ-PT6-Y</b>                                          |
|                                                                         |                                                                                 |                                                                  |                                                                           |                                                                                        |

# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

