

DH-HAC-HDW2241TMQ-Z-A-POC

2 MP Starlight HDCVI Motorized Vari-focal IR Quick-to-install Eyeball Camera



* The parameters and datasheets below can only be applied to 2241-S2-POC series.

- Max 30 fps@1080p
- Starlight, 130 dB true WDR, 3D NR
- Auto focus, 2.7 mm–13.5 mm motorized lens
- CVI/CVBS/AHD/TVI switchable
- Quick-to-install eyeball saves installation time
- Super Adapt
- Built-in mic
- Max. IR length 60m, Smart IR
- IP67, PoC (only CVI)/12V±30% DC



System Overview

Built for convenience, the PoC Series features highly reliable cameras that are powered directly by recorders on the same coaxial cable* that its videos are transmitted over. HDCVI PoC technology greatly reduces material and installation cost, making it an ideal choice for customers who are on a tight budget and are working with scenes that require complex deployment.

*We recommend choosing RG59 or RG6 cable for PoC transmission.

Functions

Starlight

With the adoption of large sized high performance sensor and large aperture lens, the camera is able to provide incomparable performance even under extreme lowlight environment. The starlight feature allows more details to be captured and accurate color to be recognized at night or in scenes with limited illumination.

Broadcast-quality Audio

Audio information is used as supplementary evidence in video surveillance applications. The HDCVI camera supports audio signal transmission over coaxial cable. In addition, it adopts unique audio processing and transmission technology that best restores source audio and eliminates noise, guaranteeing the quality and effectiveness of collected audio information.

* Audio input is available for some models of HDCVI cameras.

Wide Dynamic Range

With advanced Wide Dynamic Range (WDR) technology, Dahua HDCVI camera provides clear details in the environment of strong brightness contrast. The bright and dark area can get clear video even in high brightness environment or with backlight shadow.

Super Adapt

Embedded with intelligent algorithm, for changing external environment, camera can automatically adjust parameters to present the optimal image, and it solves the trouble of configuration.

Advanced 3DNR

3DNR is noise reduction technology that detects and eliminates random noises by comparing two sequential frames. Dahua's advanced 3DNR technology allows remarkable noise reduction with little impact to sharpness, especially under limited lighting condition. Besides, the advanced 3DNR effectively decreases the band width and saves the storage space.

Smart Illumination

The camera is designed with IR illumination for best lowlight performance. Smart IR is a technology to ensure brightness uniformity in B/W image under low illumination. Dahua's unique Smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object come closer to the camera.

Protection (IP67, wide voltage)

IP67: The camera passes a series of strict test on dust and soak. It has dust-proof function, and the enclosure can works normal after soaking in 1 m deep water for 30 minutes.

Wide voltage: The camera allows ±30% (for some power supplies) input voltage tolerance (wide voltage range), and it is widely applied to outdoor environment with instable voltage.

Easy Installation

HDCVI quick-to-install eyeball adopts quick-to-install pedestal, which can achieve easier installation than conventional eyeball. Quick-to-install camera reduces time and labor costs.

Technical Specification

Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Pixel	2 MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25 s–1/100,000 s NTSC: 1/30 s–1/100,000 s
S/N Ratio	> 65 dB
Min. Illumination	0.001 Lux/F1.6, 30 IRE, 0 Lux IR on
Illumination Distance	60 m (196.9 ft)
Illuminator On/Off Control	Auto
Illuminator Number	2 (IR light)
Pan/Tilt/Rotation Range	Pan: 0°–360° Tilt: 0°–78° Rotation: 0°–360°

Lens					
Lens Type		Motorized Vari-focal			
Auto Focus		Yes			
Mount Type		φ14			
Focal Length		2.7 mm-13.5 mm			
Max. Aperture		F1.6			
Field of View		Diagonal: 131°–35° Horizontal: 108°–30° Vertical: 56°–17°			
Iris Type		Fixed			
Close Focus Distance		0.8 m (2.6 ft)			
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.7 mm	44.1 m (144.7 ft)	17.6 m (57.7 ft)	8.8 m (28.9 ft)	4.4 m (14.4 ft)
	13.5 mm	144.8 m (475.1 ft)	57.9 m (190 ft)	28.9 m (94.8 ft)	14.8 m (48.6 ft)
	*DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation and commissioning manual/project design tool.				

Video	CVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; AHD: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; TVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; CVBS: PAL: 960 × 576H; NTSC: 960 × 480H
	Frame Rate
	Resolution
	Day/Night
	BLC
	WDR
	White Balance
	Gain Control
	Noise Reduction
	Smart IR
	Mirror
	Privacy Masking

Certifications	CE (EN55032, EN55024, EN50130-4) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
----------------	---


Port	
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Audio Input	One channel built-in mic

Power	
Power Supply	POC (only CVI)/12 V±30% DC
Power Consumption	Max6.4W (12 VDC, IR on) PoC (AT)


Environment	
Operating Temperature	–30 °C to +60 °C (–22 °F to 140 °F); < 95% (non-condensation)
Storage Temperature	–30 °C to +60 °C (–22 °F to 140 °F); < 95% (non-condensation)
Protection Grade	IP67

Structure	
Casing	Metal dome+metal cover+plastic decorative ring
Camera Dimensions	φ135 mm × 109 mm (φ5.31" × 4.28")
Net Weight	0.53 kg (1.2 lb)
Gross Weight	0.71 kg (1.6 lb)

Ordering Information		
Type	Model	Description
2 MP Camera	DH-HAC-HDW2241TMQP-Z-A-POC	2 MP Starlight HDCVI Motorized Vari-focal IR Quick-to-install Eyeball Camera, PAL
	DH-HAC-HDW2241TMQN-Z-A-POC	2 MP Starlight HDCVI Motorized Vari-focal IR Quick-to-install Eyeball Camera, NTSC
Accessories (Optional)	PFA13F	Junction Box
	PFA211W	Wall Mount Bracket
	PFA152-E	Pole Mount Bracket
	PFA10C	Mount Adapter
	PFB220C	Ceiling Mount Bracket
	PFM321D	12V 1A Power Adapter
	PFM904	Integrated Mount Tester



Dimensions (mm[inch])



Accessories

Optional:



PFA13F
Junction Box



PFA211W
Wall Mount Bracket



PFA152-E
Pole Mount Bracket



PFA10C
Mount Adapter



PFB220C
Ceiling Mount Bracket



PFM321D
12V 1A Power Adapter



PFM904
Integrated Mount Tester