


IPMECD-S-ML-M2745

Telescopic Straight Arm



- 2.7 to 4.5 m (8.56 ft to 14.76 ft) telescopic arm, suitable for both side of the barrier gate. Made of aluminum alloy with electrostatic powder coating for rust prevention. Main arm section features red/green LED strip lighting and a flexible anti-smash rubber strip at the base.

Series Overview

Constructed from highly durable aluminum alloy, the Barrier Rod features an advanced anti-rust coating on its surface. Additionally, it is equipped with an elastic anti-collision rubber strip at the bottom for added protection.

Technical Specification

Basic	
Color	Red and white
Matched Product	DHI-IPMECD 206E-XS series barrier
General	
Operating Temperature	−35 °C to +65 °C (−31 °F to +149 °F)
Storage Temperature	−35 °C to +65 °C (−31 °F to +149 °F)
Operating Humidity	10%–90% (RH), non-condensing
Storage Humidity	10%–90% (RH), non-condensing
Casing Material	Metal (aluminium)
Product Dimensions	2525 mm × 80 mm × 45 mm (99.41" × 3.15" × 1.77") (L × W × H)
Packaging Dimensions	2625 mm × 130 mm × 100 mm (103.35" × 5.12" × 3.94") (L × W × H)
Net Weight	4.1 kg (9.04 lb)
Gross Weight	4.5 kg (9.92 lb)
Installation	Install onto the matching barrier
Anti-corrosion Level	Basic Protection *The products are designed for general use and are applicable even in areas with no specific requirements for anti-corrosion protection.

Ordering Information

Type	Model	Description
Barrier Rod	IPMECD-S-ML-M2745	Telescopic Straight Arm

Dimensions (mm[inch])

