

IPMECD-0151-M1525

Barrier Rod



Series Overview

Constructed from highly durable aluminum alloy, the Barrier Rod features an advanced anti-rust coating on its surface. Additionally, it is equipped with an elastic anti-collision rubber strip at the bottom for added protection.

Technical Specification

Basic

Color	Mixed with red and white
Matched Product	DHI-IPMECD-105X series

General

Operating Temperature	−35 °C to +65 °C (−31 °F to +149 °F)
Storage Temperature	−35 °C to +65 °C (−31 °F to +149 °F)
Operating Humidity	10%–90% (RH), non-condensing
Storage Humidity	10%–90%, non-condensing
Casing Material	Metal (Aluminum)
Product Dimensions	4,000.0 mm × 100.0 mm × 45.0 mm (157.48" × 3.94" × 1.77") (L × W × H)
Packaging Dimensions	4,150.0 mm × 200.0 mm × 90.0 mm (163.39" × 7.87" × 3.54") (L × W × H)
Net Weight	7.3 kg (16.09 lb)
Gross Weight	8.9 kg (19.62 lb)
Installation	It can be Installed on the boom gate.

Ordering Information

Type	Model	Description
Barrier Rod	IPMECD-0151-M1525	Barrier Rod

- 4 m folding arm that can be used on either side of the boom gate. The main and sub parts are 1.5 m and 2.5 m respectively.
- Made of aluminum alloy, and designed with an anti-rust case that was treated with electrostatic spray.
- Elastic anti-smashing rubber strip at the bottom.

Dimensions (mm[inch])

