

DHI-PHRIA1.95-RE-G-V2

Ultimate Convenience Indoor Rental LED

Features :

- 500x500mm and 500x1000mm cabinet size design, Flexibly adapt to multiple scenarios.
- Optional Arc-shaped lock design,enable-10° ~10° at every 2.5° step,Support $\pm 10^\circ$, $\pm 7.5^\circ$, $\pm 5^\circ$, $\pm 2.5^\circ$, 0° .
- Handle type quick lock design of self-locking, Enables one engineer to finish installation.
- Dot by dot calibration ensures color richness and brightness uniformity.



Technical Specification

Model

Model	DHI-PHRIA1.95-RE-G-V2
-------	-----------------------

Parameters

Pixel Pitch	1.953mm
Pixel Configuration	1R1G1B
LED Type	SMD1415 (GOB)
Brightness (Max)	1000 nit
Color Temperature	6500K-9300K (adjustable)
Viewing Angle	H160° / V160°
Pixel Density	262,144 dots/m ²
Module Size	W250mm×H250mm
Module Resolution	128x128 dots
Cabinet Size	W500mm×H500mm×D83mm
Cabinet Resolution	256×256 dots
Cabinet Weight	7.5 kg ± 0.5
Cabinet Material	Die-cast Aluminum

Operating Temperature/ Humidity	-10℃~+40℃/10~80%RH
Storage Temperature/ Humidity	-20℃~+60℃/10~80%RH
IP Rating	Front IP20/Rear IP20
Aspect Ratio	1:1
Gray Scale	16 bits
Contrast Ratio	3000:1
Refresh Rate	7680Hz
Input Voltage	AC 110~220V (+/-10%)
Input Power (max)	630 W/m ²
Input Power (Avg)	300 W/m ²
Installation Mode	Hanging/Stacking
Module Maintenance	Front/Rear Maintenance
PSU & Others Maintenance	Rear Maintenance
Signal Transmission Distance	CAT5 Cable (L≤100m), Multi-mode fiber (L≤300m), Single-mode fiber (L≤10km)

Dimensions

