


DS-2XE2705CB-M04(316L)

316L Explosion Proof Control Box with Built-in



Key Feature

- Stainless steel 316L with anti-corrosion surface spray treatment
- 4 cable outlets
- ATEX and IECEx certified explosion-proof performance
- Ingress protection, IP68
- Purchase certified cable glands sealed with setting compound for cable routing if using electronic devices inside.

Specification

Model	DS-2XE2705CB-M04(316L)
Power	Rated input: AC 100 ~ 240V Rated output : DC 12V / 2A
Material	stainless steel 316L
Dimension	Overall Dimension: 275.0 mm × 219.5 mm × 109.1 mm (10.83" × 8.64" × 4.30"), Internal Dimension: ϕ 149.0 mm × 84.0 mm, with 1 power adapter
Package Dimension	372 mm × 372 mm × 181 mm (14.65" × 14.65" × 7.13")
Weight	Approx. 5.9 kg (13.0 lb.)
Startup and Operating Conditions	-40 ° C to 60 ° C (-40 ° F to 140 ° F). Humidity 95% or less (non-condensing)
Protection	IP66: IEC 60529-2013, IP68: IEC 60529-2013
Explosion-Proof Protection	Ex db II C T6 Gb/Ex tb IIIC T80° C Db

Available Model

DS-2XE2705CB-M04(316L)

Dimension

