

**DS-K3G225X-S**  
**Side empty cabinet**



- Side empty cabinet for G501SX&G501BX&G501CX

## ▪ Specification

| General           |                                                                                                                                        |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Pedestal material | SUS304 stainless steel 1.0 mm (mostly)                                                                                                 |
| Dimensions        | Without package: 1200 mm × 233 mm × 1000 mm (47.2" × 9.2" × 39.4")<br>With package: 1350 mm × 410 mm × 1120 mm (53.1" × 16.1" × 44.1") |
| Weight            | Net: 18.58 kg (40.96 lb); Gross: 25.8 kg (56.88 lb)                                                                                    |

## ▪ Note

The main element of the turnstile is stainless steel, which is rust less (antioxidant) and corrosion resistant (The anti-corrosion ability in the medium of acid, alkali, and salt). In order to keep the stainless steel from being oxidized or corroded, you should clean and care the turnstile surface periodically.

### The instructions and tips for maintaining the turnstile are as follows:

1. Select different stainless steel types according to the variety of the environments. You can select 304 stainless steel for common circumstances and 316 stainless steel for the scenarios of seaside and chemical plants.
2. Keep the device surface clean and dry.
3. Use non-woven cloth and ethyl alcohol to clean the dirt on the device surface.
4. Use sourcing pad (do not use mesh cleaning ball) to clean the rust on the device surface by following the wire drawing on the stainless steel. And then use non-woven cloth and stainless steel cleaner to wipe the device surface.
5. Clean and maintain the device by using non-woven cloth and stainless steel cleaner periodically. It is suggested to clean the device every month in common circumstances and every week for severe environments (seaside and chemical plants for instance).

## ▪ Available Model

DS-K3G225X-S

## ▪ Accessory

## ▪ Optional



# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

