

DS-KIS702EY **Villa Two Wire Kit**




- 2-wire digital IP video intercom kit for villa or house, only one call button
- DS-KD8003Y-IME2 x1
- DS-KH6320EY-WTE2 x1
- DS-KAD704Y x1
- DS-KAW30-2N x1

▪ Specification

Door station	
Processor	Embedded microcontroller
Operation system	Embedded Linux operation system
Operation mode	One touch key
Door station	
Camera	2MP super definition camera
Resolution	Main stream: 1920 × 1080, (720p configurable); sub stream: 720 × 480
Night vision	Support low light and IR light supplement mode
Backlight compensation	Support
Digital noise reduction	Support
WDR	True WDR
Field of view	Horizontal 146°, vertical 82°
Video Compression Standard	H.264
Stream	Main stream: 1080p@30fps, 720p@30fps (configurable); sub stream: D1
Motion detection	Support
Flash-avoid frequency	50 Hz, 60 Hz
Door station	
Audio input	Built-in omnidirectional microphone
Audio output	Loudspeaker, 20 cm sound effect > 80 db
Audio quality	Noise suppression and echo cancellation
Audio compression standard	G.711 U
Audio compression Rate	64 Kbps
Audio intercom	Full-duplex two-way audio intercom
Door station	
Sub door station capacity	16
Door station	
RS-485	1 (1 for Hikvision's sub module communication)
Debugging port	1
Lock control	2 (2 relay, max to 30 VDC, 2 A)
Alarm input	4 (2 exit buttons and 2 door contacts by default)
TAMPER switch	1
Power interface	12 VDC power output (12 V, 500 mA Max.)
Door station	
Working temperature	-40 °C to 60 °C (-40 °F to 140 °F)
Working humidity	10% to 90%
Installation	Surface mounting
Protection level	IP 65
Button	1
Power input	Powered by KAD704Y or KAD706Y series distribution
Indoor station	
Operation system	Embedded Linux operation system
Memory	128 MB

Flash	32 MB
Indoor station	
Displays screen	7-inch TFT LCD
Display resolution	1024 × 600
Operation method	Capacitive touch
Indoor station	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Audio quality	Noise suppression and echo cancellation
Volume	Local or software control
Audio compression standard	G.711 U, G.711 A
Audio compression Rate	64 Kbps
Indoor station	
Wired network	Two-wire network
Wireless network	Wi-Fi 802.11b/g/n
Protocol	TCP/IP, SIP, RTSP
Indoor station	
Network interface	Two-wire interface
RS-485	1
Alarm input	8 zones alarm input
Relay output	2
TF card	Support, Max. 128 GB
Indoor station	
Power supply	Powered by KAD704Y or KAD706Y series distributor
Power consumption	≤ 4 W
Working temperature	-10 °C to 50 °C (14 °F to 122 °F)
Working humidity	10% to 90%
Dimensions (W × H × D)	200 mm × 140 mm × 23.6 mm (7.87" × 5.51" × 0.93")
Video Audio Distributor	
Network interface	1 RJ45
Two-wire interface	6 (2 for cascading and 4 for devices)
Signal indicator	6
Power indicator	1
Reset	1
Video Audio Distributor	
Power supply	24 VDC
Power consumption	CH1 to CH3 < 4 W, CH4 < 8 W
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working humidity	10% to 90%

▪ Dimension



▪ **Accessory**

▪ **Optional**

DS-KH6320Y-WTE2 #EU-W	DS-KD8003-IME2	DS-KAD704	DS-KH6320-WTE2# EU&UK	DS-KAW30-2N
				
DS-KD8003-IME2/S	DS-KH6320Y-WTE2	DS-KH6320-WTE2	DS-KH6320EY-WTE 2	DS-KABD8003-RS1
				
DS-KH6320Y-WTE2 #EU				
				

See Far, Go Further



www.hikvision.com
support@hikvision.com

