

DHI-ISC-ETRR2A-T302

RF Waythcare-R Cable Lock T302-2A 25cm



Introduction

As an EAS electronic tag, the automatic unlocking alarming tag can be automatically unlocked by remote control. By physically bound to goods, it prevents product theft and effectively reduces losses for merchants.

Features

Super Protection Capacity

The sound and light alarm will be triggered when the wire rope is cut by external force and the alarm volume is not less than 90 dB.

Remote Unlocking

The tag will be automatically unlocked after the unlocking instruction is issued by the remote control, which greatly reduces the work intensity of the cashier and improves the cashier efficiency.

EAS Alarm Function

Supports EAS antenna recognition (RF) and 2A alarm.

Low Power Consumption

More than 3-year service life (unlock 2 times a day).

Innovative Appearance

Exquisite and compact. Comfortable ergonomic design meets the protection needs of high-end products without affecting the display of products.

Detachable Lanyard Design

Equipped with detachable design, the Cable Lock is flexible and convenient, and suitable for various scenarios.

Scene

The tag can be fixed on small and medium-sized valuable goods.

Technical Specification

Performance

Model	DHI-ISC-ETRR2A-T302
Technology	Radio-Frequency (RF)
Detection Frequency	8.2 MHz $\pm$ 0.25 MHz

- Built in alarm function, triggered when tag or net damaged.
- High detection rate and excellent anti-theft effect.
- Can be remotely unlocked.
- Detachable lanyard design, flexible and convenient.
- Environmentally friendly and economical, can be reused after unlocking.

AM Antenna Detection Distance	$\leq$ 0.8 m (Based on system performance)
Shell Material	ABS
Unlocking Method	Electrical Machinery
Certifications	Conform with RoHS Directive 2011/65/EU, 2015/863/EU and REACH regulations as defined in EC No 1907/2006 and subsequent amendments.

General Parameters

Alarm Sound Pressure	$\geq$ 90 dB
Alarm Duration	5 min $\pm$ 10 s
Low Battery Alert	Yes
Battery Model	CR2032 $\times$ 2
Battery Life	$\geq$ 3 years
Flashing Interval	30 s $\pm$ 2 s
Lanyard Type	Metal Cable
Tensile Capacity	$\geq$ 350N
Color	Black
Lanyard Length	3.6 mm $\times$ 250 mm (0.14" $\times$ 9.84")
Bare Machine Dimensions	71 mm $\times$ 44.5 mm $\times$ 23 mm (2.80" $\times$ 1.75" $\times$ 0.91")
Inner Box Dimensions	93 mm $\times$ 55 mm $\times$ 28 mm (3.66" $\times$ 2.17" $\times$ 1.10")
Net Weight (Single One)	0.0495 kg (0.109 lb)
Gross Weight	0.0560 kg (0.123 lb)
Packaging Dimensions	380 mm $\times$ 280 mm $\times$ 150 mm (14.96" $\times$ 11.02" $\times$ 5.91")
Packaging	1 pc per Box, 100 pcs per Carton
Carton Weight	5.6 kg (12.35 lb)
Sales Unit	pc

Environmental Constraints

Temperature	0 °C to 50 °C (32 °F to 122 °F)
Humidity	20 % - 60 % (RH)

Ordering Information		
Type	Model	Description
Alarming Tag	DHI-ISC-ETRR2A-T302	RF Waythcare-R Cable Lock T302-2A 25cm