

DS-D5024F2-BV2S**23.8 inch FHD 100Hz VA Monitor with speaker**

- VA technology , 178° ultra-wide view screen.
- 8 bit LVDS FHD (1920×1080) display.
- 100 Hz refresh rate, more fluid and life-like video.
- Ultra-thin device body with ultra-thin border for 3 sides.
- 3D noise reduction.
- Low blue light design for eye care.
- Dual interface of HDMI and VGA.
- Support VESA wall mount.
- Built-in speaker for audio input.

▪ Specification

Display	
Screen Size	23.8 inch, 60.45 cm
Active Display Area	527.04 (H) mm × 296.46 (V) mm, 15.62 dm ²
Resolution	1920 × 1080
Backlight	E-LED
Pixel Pitch	0.2745 (H) mm × 0.2745 (V) mm
Brightness	250 cd/m ²
Viewing Angle	178° (H) / 178° (V)
Color Depth	8 bit, 16.7 M
Contrast Ratio	4000 : 1
Response Time	7 ms
Refresh Rate	Typ. 60 Hz , Max. 100Hz
Haze	Haze 25%
Reliability	7 × 24 H
Color Gamut	72% NTSC
Interface	
Video & Audio Input	HDMI 1.4 × 1, VGA × 1, Audio IN × 1
Video & Audio Output	Speaker × 2 (4Ω 2W)
Data Transmission Interface	None
Control Interface	None
Power	
Power Supply	DC 12V, 2.0A
Power Consumption	≤ 24 W
Standby Consumption	≤ 0.5 W
Working Environment	
Working Temperature	0°C to 40 °C (32 °F to 104 °F)
Working Humidity	20% to 90% RH (Non-Condensing)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Storage Humidity	10% to 90% RH (Non-Condensing)
General	
Casing Material	Plastic
VESA	75 mm × 75 mm (4 - M4 × 6 mm)
Bezel Width	2.0 mm (top/left/right), 23.55 mm (bottom)
Product Dimensions (W × H × D)	With base: 539.7 (W) mm × 399.9 (H) mm × 164.72 (D) mm 21.25 (W) inch × 15.74 (H) inch × 6.49 (D) inch Without base: 539.7 (W) mm × 327.33 (H) mm × 43.5 (D) mm 21.25 (W) inch × 12.89 (H) inch × 1.71 (D) inch
Package Dimensions (W × H × D)	611 (W) mm × 405 (H) mm × 118 (D) mm (24.06(W) × 15.94(H) × 4.65 (D)) inch
Standby Time	600s
Net Weight	2.85 ± 0.5 kg
Gross Weight	3.85 ± 0.5 kg
Packing List	Monitor × 1, Base component × 1, Power adapter (12 V, 2 A) × 1, HDMI cable (1.5 m) × 1, User manual × 1, Multilingual manual × 1


Remarks	The base is included by default. The product appearance and parameters in this specification may vary from your actual device. Please consult our local sales staff for further information
---------	---

Physical Interface

Interface	Description	Interface	Description
HDMI	HDMI 1.4 digital signal input interface	VGA	VGA analog signal input interface
Audio IN	3.5mm Audio input interface	DC	DC 12V 2.0A input interface

HDMI	VGA	↻	DC
------	-----	---	----

Dimension



Accessory

Optional

DP-D501940-1X1-Q

1-NW-Q0.1-TY/V20

DS-DM1940W

0



See Far, Go Further



www.hikvision.com
support@hikvision.com

