

DS-PA201PG-32WE Control Panel



- Simple and elegant appearance design
- Wi-Fi and GPRS network for cloud communication
- Friendly app interface makes installation and use easier
- Up to 2000 m radio signal transmission range in open space

▪ Specification

Capacity	
ARC	1
Installer	3
User	12
Areas	8
Wireless zones	32
Wireless keypads	4
Wireless sounders	4
Admin	1
Logs	1000
Wireless keyfobs	16
Communication	
Transmission technology	868.0-868.6 MHz
Transmission range (free space)	Up to 2,000 m (Between control panel and detectors/peripherals in open space and without nearby frequency band interference). *In actual applications, the maximum transmission distance may be affected by Radio Frequency environment and depends on the connected devices.
Maximum effective radiated power (ERP)	25 mW max
Radio signal modulation	2GFSK
Encryption	AES-128
Ethernet	1 8P8C socket
Ethernet speed	≤10Mbps
Wi-Fi	802.11 b/g/n
Cellular	GPRS
SIM slots	1
Software features	
Upgrade OTA	Yes
Protocol	SIA-DCS *SIA-DCS ADM-CID *ADM-CID OTAP Other proprietary protocols
Notifications	
APP notifications	Yes
SMS notifications	Yes
Calls notifications	No
ARC notifications	Yes
Event types	Alarms Faults System Events Operations

Indication	
Indication method	LED
Hardware features	
Tamper-Proof	Yes
Power Supply	
Mains power	110-240 V~, 50/60 Hz
Power consumption	max current: 0.2 A quiescent current: 90 mA
Electrical characteristics	
Built-in backup battery	Yes
Battery life	Up to 12 hours at normal temperature *Under standalone mode without control panel actions (arm or alarm trigger). Battery life may be reduced due to low environmental temperature.
General	
Dimension (W×H×D)	165 x 165 x 37.5 mm
Weight	407 g
Operation temperature	-10 °C to +55 °C
Operation humidity	10% to 90%
Shell material	Plastic

▪ Available Model

DS-PA201PG-32WE

DS-PA201PG-32WE(RU)

▪ Accessory

▪ Optional

DS-PZ201ADB-CO M	DS-PC201N
	

See Far, Go Further



www.hikvision.com
support@hikvision.com

