

ITSZJ-3701-PTZ

Camera Bracket



Scene

The Traffic Motorized Bracket is compatible with illuminators and the All-in-One Enforcement Camera. Through it, the angle of the camera and illuminator can be remotely adjusted for optimal results.

Technical Specification

General	
Product Dimensions	224 mm × 170 mm × 284 mm (8.82" × 6.69" × 11.18") (L × W × H)
Operating Temperature	−25 °C to +55 °C (−13 °F to +131 °F)
Storage Temperature	−25 °C to +55 °C (−13 °F to +131 °F)
Operating Humidity	≤95%
Storage Humidity	≤95%
Net Weight	6.55 kg (14.44 lb)
Protection	IP55
Power Supply	12 VDC
Port	
RS-485	One RS-485 port, which is used for connecting the camera

Ordering Information

Type	Model	Description
Camera Bracket	ITSZJ-3701-PTZ	Camera Bracket
Accessories (Optional)	3702	Pole Mount Bracket (purchase separately)
	3013	Wall Mount Bracket (purchase separately)

- Transmits through the stepper motor driver and the gear box.
- Communicates through RS-485 bus and supports Pelco-D and Pelco-P protocols.
- The baud rate reaches 1,200 bps, 2,400 bps, 4,800 bps, and 9,600 bps.
- The horizontal rotation of the PTZ is 0°–15° per second, and the vertical rotation is 0°–2° per second.
- The horizontal range of the PTZ's pan and tilt is ± 30°, and the vertical range is is −70° to +20°.
- Supports 12 VDC output.
- IP55 rated.

Accessories



Optional:



3702
Pole Mount Bracket
(purchase separately)



3013
Wall Mount Bracket
(purchase separately)



Dimensions (mm [inch])

