

DS-7708NXI-K4/8P(E)(NEU)
8-ch PoE 1.5U K Series AcuSense 4K NVR



- Automatic speed control fans are designed for running quietly and energy saving
- Adopt Hikvision AcuSense technology to minimize manual effort and security costs
- Efficient playback with AcuSearch technology
- Accurate perimeter protection effectively reduces false alarms
- Automatic cameras connection and configuration
- Up to 8-ch IP camera inputs, plug & play with 8 Power-over-Ethernet (PoE) interfaces
- H.265+/H.265/H.264+/H.264 video formats
- Up to 3-ch@12 MP or 5-ch@8 MP or 8-ch@4 MP or 8-ch@2 MP decoding capacity
- Up to 80 Mbps incoming bandwidth

▪ Specification


Model		DS-7708NXI-K4/8P(E)(NEU)
Intelligent Analytics	AI by NVR	Facial recognition, perimeter protection, motion detection 2.0, AcuSearch
	AI by Camera	Facial recognition, perimeter protection, motion detection 2.0, ANPR
AcuSearch	By Camera	All channels *: The camera should enable AcuSearch function
Perimeter Protection	By NVR	Video analysis (HD network camera, H.264/H.265) for human and vehicle recognition to reduce false alarm. Up to 4 MP: 2-ch; 8 MP to 5 MP: 1-ch
	By Camera	All channels
Facial Recognition	Facial Detection and Analytics	Face picture comparison, human face capture, face picture search
	Facial Detection and Analytics Performance	Up to 4 MP: 2-ch; 8 MP to 5 MP: 1-ch
	Face Picture Comparison	8-ch
	Face Picture Library	Up to 16 face picture libraries, with up to 50,000 face pictures in total (each picture ≤ 1 MB, total capacity ≤ 1 GB)
Motion Detection 2.0	By NVR	All channels, up to 4 MP (when enhanced SVC mode is enabled, up to 8 MP) video analysis for human and vehicle recognition to reduce false alarm
	By Camera	All channels
Video and Audio	IP Video Input	8-ch
	IP Speaker Input	4-ch
	Incoming Bandwidth	80 Mbps
	Outgoing Bandwidth	160 Mbps
	HDMI Output	1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
	VGA Output	1-ch, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
	Video Output Mode	HDMI/VGA independent output
	Audio Output	1-ch, RCA (Linear, 1 KΩ)
	Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ, using the audio input)
Decoding	Decoding Format	H.265, H.265+, H.264, H.264+
	Recording Resolution	16 MP/12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF *: 16 MP is only available for channel 1.
	Synchronous	8-ch

	Playback	
	Decoding Capability	AI on: 2-channel 12 MP@30 fps, 4-channel 8 MP@30 fps, 5-channel 6 MP@30 fps, 8-channel 4 MP@30 fps, 8-channel 3 MP@30fps, 8-channel 2 MP@30fps AI off: 3-channel 12 MP@30 fps, 5-channel 8 MP@30 fps, 6-channel 6 MP@30 fps, 8-channel 4 MP@30 fps, 8-channel 3 MP@30fps, 8-channel 2 MP@30fps
	Stream Type	Video, Video and Audio
	Audio Compression	G.711ulaw/G.711alaw/G.722/G.726/AAC/MP2L2
Network	Remote Connection	128
	API	ONVIF (profile S/G); SDK; ISAPI
	Compatible Browser	IE 11, Chrome 91, Firefox 88, Safari 12, Edge 91, or above version
	Network Protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS
	Network Interface	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces
PoE	Interface	8, RJ-45 10/100 Mbps self-adaptive Ethernet interface
	Power	≤ 150W
	Standard	IEEE 802.3af/at
Auxiliary Interface	SATA	4 SATA interfaces
	Capacity	Up to 16 TB capacity for each HDD
	Serial Interface	2 RS-485 (half-duplex), 1 RS-232
	eSATA	NA
	Alarm In/Out	16/4
	USB Interface	Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0
	Ctrl 12V	NA
	DC 12V	Support
General	GUI Language	English, Russian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Turkish, Japanese, Danish, Swedish, Norwegian, Finnish, Korean, Traditional Chinese, Thai, Estonian, Vietnamese, Croatian, Slovenian, Serbian, Latvian, Lithuanian, Uzbek, Kazakh, Arabic, Hebrew, Ukrainian, Indonesian
	Fan	Supports
	Power Supply	100 to 240 VAC, 50 to 60Hz
	Consumption	≤ 50 W (without HDD)
	Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Working Humidity	10 to 90 %
	Dimension (W × D × H)	440 × 391 × 72 mm (17.32 × 15.39 × 2.82 inch)
	Weight	≤ 5kg (without HDD, 10 lb.)
Certification	CE	EN 55032: 2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4, EN 55035: 2017
	Obtained	CE, CB, REACH, WEEE, UKCA, RCM, IC

▪ Function


▪ Physical Interface

DS-7708NXI-K4/8P(E)



Number	Description	Number	Description
1	Poe interfaces	8	RS-232 interface
2	USB 3.0 interface	9	ALARM IN
3	LAN network interface	10	ALARM OUT
4	AUDIO OUT	11	RS-484 interface
5	AUDIO IN	12	GND
6	HDMI interfaces	13	Power supply
7	VGA interface	14	Power switch

DS-7708NXI-K4/8P(E)/IO16+9





No.	Description	No.	Description
1	PoE interfaces	9	RS-232 serial interface
2	USB 3.0 interface	10	ALARM IN
3	LAN network interface	11	ALARM OUT
4	eSATA interface	12	RS-485 interface
5	AUDIO OUT	13	GND
6	AUDIO IN	14	Power supply
7	HDMI interface	15	Power switch
8	VGA interface		

▪ Available Model

DS-7708NXI-K4/8P(E)(NEU)

▪ Dimension



See Far, Go Further



www.hikvision.com
support@hikvision.com

